



规格说明:Specifications:

电气特性:Electrical:

1. 额定电流: Current Rating  
**1.5A/contact terminal**
2. 额定电压: Voltage Rating  
**30V DC**
3. 接触阻抗:Contact Resistance  
**30 milliohms MAX**
4. 耐电压:Dielectnic Withstanding Voltage:  
**500 V AC AT Sea Level**
5. 绝缘阻抗:Insulation Resistance:  
**1000MEGA ohms MIN**

物理性能:Mechanical:

1. 插拔力: Cnnector Mate and Unmate Force  
**Mate force:3.57kgf(MAX)**  
**Unmate force:1.02kgf(MIN)**
2. 端子保持力: Terminal Retention  
**1.2kgf(MIN)**

原材料:Matorial:

1. 塑胶:Housing:  
**Hing Temperature Ternmaplastics,**  
**PBT White/Black**
2. 端子:Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

1. 端子:Contact: Plated Gold in Mating Area;  
**Tin On Solder Talls**
2. 外壳:Shell:  
**Nickel Plating**



UNLESS OTHERWISE SPECIFIED TOLERANCE

- .X ±0.20
- .XX ±0.15
- .XXX ±0.10
- ANG. ±2'

DRAWN	H.Q.huocy
APPROVED	
DATE	2011.03.18

UNIT	MM
SCALE	3/1
SIZE	A4

TITLE	USB A母双层直插14.2MM四脚
PART NO.	
DOC. NO.	

REV. A